

(12) United States Patent

Miyamoto et al.

(10) Patent No.:

US 6,263,939 B1

(45) Date of Patent:

Jul. 24, 2001

(54) OPTICAL INFORMATION MEDIUM, AND METHOD AND APPARATUS FOR FABRICATING THE SAME

(75) Inventors: Hisaki Miyamoto, Suita; Michiyoshi

Nagashima, Ikoma; Kiyoshi Inoue, Osaka; Sakae Noda, Katano, all of (JP)

(73) Assignee: Matsushita Electric Industrial Co.,

Ltd., Osaka (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 09/366,935

Feb. 15, 1995

(22) Filed: Aug. 4, 1999

Related U.S. Application Data

(62) Division of application No. 08/861,943, filed on May 22, 1997, now Pat. No. 5,972,250, which is a division of application No. 08/599,181, filed on Feb. 9, 1996, now Pat. No. 5,681,634.

(30) Foreign Application Priority Data

		(JP)	
(51)	Int. Cl. ⁷	В32В	31/28
(52)	U.S. Cl.		56/74;
		156/285: 156/205: 156	D757

(JP) 7-27086

(56) References Cited

U.S. PATENT DOCUMENTS

4,670,077	6/1987	Peeters .	
4,995,799 *	2/1991	Hayashi et al	425/111
5,023,167	6/1991	Kalyanaraman et al	

5,296,340		3/1994	Tsukada et al	
5,470,691		11/1995	Arai et al	
5,549,952		8/1996	Arai et al	
5,705,247		1/1998	Arai et al	
5,744,193	٠	4/1998	Kitano	156/74
5,800,670	٠	9/1998	Kitano	156/74
5,843,257	٠	12/1998	Inouchi	156/74

FOREIGN PATENT DOCUMENTS

63119040	5/1988	(JP) .
3209640	9/1991	(JP).
351782	11/1991	(JP) .
4-271031	9/1992	(JP) .
6274940	9/1994	(JP).
750035	2/1995	(JP) .
706178	4/1996	(JP).
94-8469	4/1994	(KR).

OTHER PUBLICATIONS

Korean Patent office Action in corresponding Korean Application No. 96-3660, dated Oct. 28,1998 (4 pp.).


* cited by examiner

Primary Examiner—Michael W. Ball Assistant Examiner—Michael A. Tolin (74) Attorney, Agent, or Firm—Renner, Otto, Boisselle & Sklar, LLP

(57) ABSTRACT

The disk-shaped optical information medium of this invention includes: a first substrate having a center hole; a second substrate having a center hole; and a radiation curable resin interposed between the first and second substrates for bonding together the first and second substrates, wherein the optical information medium further includes a stopper for preventing the radiation curable resin from protruding into the center holes of the substrates, and a space between the first and second substrates of at least a half of a clamp region for clamping the optical information medium is filled with the resin.

9 Claims, 17 Drawing Sheets



427/240